



2000 Ottawa YT-30 4 x 2 On-Highway Yard Truck



Serial #301137

VIN# 11VA813E4YA000511

FEATURES

- Cummins ISB Electronic 205 HP @ 2300 RPM, 520 LB/FT Torque @ 1600 RPM
- Allison Model MT-643 (4 Speed) Automatic Transmission
- Meritor/Rockwell Model FF-961 12,000 lb. Front Axle with 15.5" x 4" Brakes
- Meritor/Rockwell Model RS-24 160 30,000 lb. Rear Axle, 7.17:1 Ratio
- Gear Box Type Power Steering with Mechanical Back Up
- ★ 116" Wheelbase with "L" Frame Reinforcement
- ★ 50,000 lb. Yield 3/8" Formed Mainframe, RBM: 1,835,000-in. lbs. Per Rail For a Total of RBM: 3,670,000 on Both Rails
- 8.25 X 22.5 10 Hole Steel Disc Wheels
- ★ 5 Digit Hour Meter Mounted on Left Side
- Holland Model FW-3500 Fifthwheel with Automatic Latch and Driver Controlled Unlatch –Rated @ 70,000 lbs., 70,000 lb. Lift Rated 5" I.D. Hydraulic Cylinders 17" Lift
- ★ Fifthwheel in Upright Position from Center Point to Back of Cab is 79"
- ★ 50 Gallon Rectangular Step Tank
- 55 Degree Tapered Deck and Bumper Curbside Front
- 3 PT Cab Air Ride Suspension
- Electric Tilt System For Cab
- 40,000 BTU Heater/Defroster
- Cab and Deck Undercoating
- Side and Rear Cab Doors
- Tinted Glass all Windows
- Vertical Exhaust with Heat Shield
- Front Tow Hooks and Rear Tow Eyes
- 15.2 CFM Cummins/Wabco Air Compressor
- (3) 12 Volt Low Maintenance Batteries
- Leese Neville 105 Amp Alternator
- Paint: Cab – White
Chassis – Black
Wheels – White
- Electric Back Up Alarm
- Legal Width Side Step
- See-Thru Sunvisor
- Air Ride Seat with Retractable Seat Belt
- ICC Light Package
- Electric Windshield Washer
- Speedometer
- 5 Digit Hour Meter
- Cab Marker Lights
- 7-Wire Coiled Trailer Light Cable
- Automatic Slack Adjusters on Steer Axle

Serial #301137

- Automatic Slack Adjusters on Drive Axle
- Mud Flaps Behind Drive Axle
- ★ Strobe Light
- ★ Cab Fan
- ★ 8" Convex Mirrors
- ★ Raised Roof Cab
- ★ Sludge Remover System
- ★ Jump Start Stud
- ★ Front Shocks
- ★ Fire Extinguisher



Mid-Pacific Industries, Inc.
1500 Case Place
Woodland, CA 95776
Tel 530-661-6777
Fax 530-661-9595